

TK-TEAM Touch Screen L06PA

Model		65-L06PA	75-L06PA	86-L06PA
Display	Size	65 inch	75 inch	86 inch
	Type	a-Si TFT-LCD	a-Si TFT-LCD	a-Si TFT-LCD
	Aspect Ratio	16:9	16:9	16:9
	Backlight	LED	LED	LED
	Resolution	3840×2160	3840×2160	3840×2160
	Refresh Rate	60Hz	60Hz	60Hz
	Brightness	400nits	400nits	400nits
	Contrast Ratio	5000:1	5000:1	5000:1
	Viewing Angle	178°	178°	178°
	Colors	1.07B(10 bits)	1.07B(10 bits)	1.07B(10 bits)
	Life(MTBF)	≥120,000H	≥120,000H	≥120,000H
	Touch Area(L*W)/mm	1454.01*831.60	1675.35*956.14	1919.03*1092.14
	Display Area(L*W)/mm	1428.48*803.52	1650.24*928.26	1895.04*1065.96
	Glass Material	AG(anti-glare) tempered glass Reflectivity<1%	AG(anti-glare) tempered glass Reflectivity<1%	AG(anti-glare) tempered glass Reflectivity<1%
Glass Thickness	3mm	3mm	3mm	
Glass Hardness	Mohs 7	Mohs 7	Mohs 7	
Bonding	0 gap	0 gap	0 gap	
Speaker	/	20W*2	20W*2	20W*2
Power	/	AC:100-240V;60/50Hz; 300W(Max); ≤0.5W(Standby)	AC:100-240V;60/50Hz; 430W(Max); ≤0.5W(Standby)	AC:100-240V;60/50Hz; 550W(Max); ≤0.5W(Standby)
Android	Version	Android 11	Android 11	Android 11
	CPU	Cortex A73*4 1.8GHz	Cortex A73*4 1.8GHz	Cortex A73*4 1.8GHz
	GPU	Mali-G52 2EE MC2 800MHz	Mali-G52 2EE MC2 800MHz	Mali-G52 2EE MC2 800MHz
	RAM	4G DDR4	4G DDR4	4G DDR4
	ROM	32G	32G	32G
	Ethernet	10/100/1000Mbps standard: IEEE	10/100/1000Mbps standard: IEEE	10/100/1000Mbps standard: IEEE
	WiFi	802.11a/b/g/n/ac(2.4GHz+5GHz)	802.11a/b/g/n/ac(2.4GHz+5GHz)	802.11a/b/g/n/ac(2.4GHz+5GHz)
	Bluetooth	5.2	5.2	5.2
Analog Signal	VGA Compatible:VGA,SVGA,XGA,WUXGA,SXGA			
Connection	Front	HDMI 2.0 in*1	HDMI 2.0 in*1	HDMI 2.0 in*1
		Type C	Type C	Type C
		USB-A 3.0*3	USB-A 3.0*3	USB-A 3.0*3
		Touch USB-A 2.0*1	Touch USB-A 2.0*1	Touch USB-A 2.0*1
		DP 1.2 in*1	DP 1.2 in*1	DP 1.2 in*1
		HDMI 2.0 in*3	HDMI 2.0 in*3	HDMI 2.0 in*3
		VGA in*1	VGA in*1	VGA in*1
	Rear	VGA Audio in(3.5mm)*1	VGA Audio in(3.5mm)*1	VGA Audio in(3.5mm)*1
		AV in*1	AV in*1	AV in*1
		Mic in*1	Mic in*1	Mic in*1
		HDMI 2.0 out*1	HDMI 2.0 out*1	HDMI 2.0 out*1
		Spdif out(Optical)*1	Spdif out(Optical)*1	Spdif out(Optical)*1
		Line out(3.5mm)*1	Line out(3.5mm)*1	Line out(3.5mm)*1
		Public USB-A 3.0*2	Public USB-A 3.0*2	Public USB-A 3.0*2
Android USB-A 2.0*1	Android USB-A 2.0*1	Android USB-A 2.0*1		
Touch USB-B 3.0*1	Touch USB-B 3.0*1	Touch USB-B 3.0*1		
RJ45*2	RJ45*2	RJ45*2		
WiFi antenna*2	WiFi antenna*2	WiFi antenna*2		
BT antenna*1	BT antenna*1	BT antenna*1		
RS232*1	RS232*1	RS232*1		
Touch	Touch Performance	Technology:Infrared; Minimum Touch Object:≥1mm; Touch Precision:1mm; Positioning Precision:<2mm.		
	Touch Durability	≥60,000,000 times.(More than 100,000 hours)		
	Touch Points	32-point touch, 20-point writing		
	Touch Tools	Fingers, pens, or other untransparent objects.		
	Sliding Speed	Single touch:≥2.5m/s, Multi touch:≥1m/s.		
	Response Time	Single touch:<5ms, Dual touch:<7ms.		
	Light Resistance	Work normally under 80,000 lux illumination(Full daylight ≈ 100,000 lux)		
	OS Compatibility	Windows XP/7/8/10; Linux; Chrome OS; Mac OS; Android		
	Touch Features	Driver-free, calibration-free, waterproof, dustproof, ultra-thin, light.		
	Power Supply	<2W, DC 5V±5%, electric current<500mA.		
Dimension & Weight	Physical Dimensions (L*W*T)/mm	1490.80*922.46*84.75 (without wall mount)	1712.16*1047.22*84.95 (without wall mount)	1957.96*1185.20*84.95 (without wall mount)
		1490.80*922.46*116.95 (with wall mount)	1712.16*1047.22*117.15 (with wall mount)	1957.96*1185.20*112.15 (with wall mount)
	Physical Dimensions+Camera (L*W*T)/mm	1490.80*935.04*84.75 (without wall mount)	1712.16*1059.58*84.95 (without wall mount)	1957.96*1197.78*84.95 (without wall mount)
		1490.80*935.04*116.95 (with wall mount)	1712.16*1059.58*117.15 (with wall mount)	1957.96*1197.78*112.15 (with wall mount)
	Packed Dimensions(L*W*H)/mm	1690*210*1060	1920*210*1150	2154*230*1354
	Bezel Width(mm)	Left/right/Top:18.40 Bottom:72.40	Left/right/Top:18.40 Bottom:72.40	Left/right/Top:18.40 Bottom:72.40
		Left/right:18.40 Top:31	Left/right:18.40 Top:31	Left/right:18.40 Top:31
Net Weight	42Kg±1Kg	54Kg±1Kg	68Kg±1Kg	
Gross Weight	54Kg±1Kg	68Kg±1Kg	88Kg±1Kg	
Environmental Requirement	/	Operation temperature:0~40°C; Operation humidity:20%~80%RH		
In The Box	/	Pen*2 / power cable*1(3 meters) / HDMI cable*1(3 meters) / USB cable*1(A-A, 3 meters) / manual*2(1 for All-in-one touch screen, 1 for wall mount) / installation guide*1 / warranty card*1 / qualified certificate*1 / packing list*1		
Installation	/	Standard: wall mount; Optional: mobile floor stand.		